

Type : 3EL080M4C-PC-A0-000

Date : 01.01.2023

Power [kW]	: 0.55	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Y	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 080M
Pole Number	: 4	Weight [kg]	: 10.5
Nominal Speed [rpm]	: 1450	Insulation Class	: F [155°C]
Nominal Current [A]	: 1.34	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 3.62	Protection Class	: IP55
Nominal Efficiency [η]	: 80.8	Vibration Severity Grade	: A
Power Factor [cosφ]	: 0.73	Method of Cooling	: IC411 (TEFC)
Locked Rotor Current [Ia/In]	: 5.9	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.1	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.0	Motor Thermal Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 50

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	Cosφ	Cl
Δ	230	50	0.55	1450	2.32	80.8	80.4	77.0	0.73	IE3
Y	400	50	0.55	1450	1.34	80.8	80.4	77.0	0.73	IE3
Y	460	60	0.55	1750	1.17	82.1	81.7	79.0	0.72	IE3
Y	460	60	0.64	1750	1.31	82.2	81.8	79.1	0.74	IE3


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.00200
Bearing [DS / NS]	: 6204ZZ / 6204ZZ
Frame Material	: Aluminum
Flange Type / Material	: B14 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M20x1.5
Terminal Box Blind Cap	: M16x1.5
Contact Screw Thread	: M4

MECHANICAL DIMENSIONS



Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO COMMISSION REGULATION (EU) 2019/1781 THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EL080M4C-PC-A0-000

Date : 01.01.2023


NAMEPLATE DATA

Power [kW]	: 0.55	Nominal Speed [rpm]	: 1450
Nominal Voltage [V]	: 400	Nominal Current [A]	: 1.34
Connection Type [Δ / Y]	: Y	Nominal Moment [Nm]	: 3.62
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 80.8

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	24.1	78.9
P ₂	50	100	23.1	68.4
P ₃	25	100	19.2	56.5
P ₄	90	50	12.7	78.0
P ₅	50	50	9.5	72.5
P ₆	50	25	7.3	63.4
P ₇	25	25	4.9	56.0

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EL080M4C-PC-A0-000

Torque and Current Curves Related to Speed



Motor Code : 3EL080M4C-PC-A0-000

Performance Curves Related to Rated Output

