

Type : 3EL112M2C-PD-B0-000

Date : 01.01.2023

Power [kW]	: 4.00	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 112M
Pole Number	: 2	Weight [kg]	: 29.4
Nominal Speed [rpm]	: 2915	Insulation Class	: F [155°C]
Nominal Current [A]	: 7.28	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 13.1	Protection Class	: IP55
Nominal Efficiency [η]	: 88.1	Vibration Severity Grade	: A
Power Factor [cosφ]	: 0.90	Method of Cooling	: IC411 (TEFC)
Locked Rotor Current [Ia/In]	: 7.5	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.6	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.9	Motor Thermal Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 65

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	Cosφ	Cl
Δ	400	50	4.00	2915	7.28	88.1	88.8	88.2	0.90	IE3
Y	690	50	4.00	2915	4.20	88.1	88.8	88.2	0.90	IE3
Δ	460	60	4.00	3510	6.20	89.0	88.9	88.2	0.91	IE3
Δ	460	60	4.55	3500	6.97	89.0	88.9	88.7	0.92	IE3


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.00618
Bearing [DS / NS]	: 6206ZZ / 6206ZZ
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M25x1.5
Terminal Box Blind Cap	: M25x1.5
Contact Screw Thread	: M5

MECHANICAL DIMENSIONS



Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023



ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (282) 726 92 94

TECHNICAL DATASHEET ACCORDING TO COMMISSION REGULATION (EU) 2019/1781 THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

Type : 3EL112M2C-PD-B0-000

Date : 01.01.2023


NAMEPLATE DATA

Power [kW]	: 4.00	Nominal Speed [rpm]	: 2915
Nominal Voltage [V]	: 400	Nominal Current [A]	: 7.28
Connection Type [Δ / Y]	: Δ	Nominal Moment [Nm]	: 13.1
Nominal Frequency [Hz]	: 50	Nominal Efficiency [η %]	: 88.1

THE POWER LOSSES AT SEVEN OPERATING POINTS ACCORDING TO COMMISSION REGULATION (EU) 2019/1781

Operating Point Number	Speed n/n_N [%]	Torque T/T_N [%]	Relative Power Losses P_L/P_N [%]	Efficiency η [%]
P ₁	90	100	12.6	87.7
P ₂	50	100	11.7	81.1
P ₃	25	100	8.8	74.0
P ₄	90	50	6.4	87.6
P ₅	50	50	4.2	85.6
P ₆	50	25	2.6	82.8
P ₇	25	25	1.6	79.3

MAP OF RELATIVE POWER LOSSES P_L/P_N [%]



Manufactured and tested in accordance with IEC 60034


FR.AG.010 REV.NO: 04 REV.DATE: 01.01.2023

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.

Motor Code : 3EL112M2C-PD-B0-000

Torque and Current Curves Related to Speed



Motor Code : 3EL112M2C-PD-B0-000

Performance Curves Related to Rated Output

